



## OFFSET DISCS

» Models SD550, SD650, SD750, SD1050



» Models SD550, SD650, SD750, SD1050

OFFSET DISCS



MODEL	SD550		SD650	
<b>Blade Spacing</b>	9" (230 mm)	10.5" (267 mm)	10.5" (267 mm)	12" (305 mm)
Width, working	6.5' to 20' (1.9 to 6.1 m)	6' to 20' (1.8 to 6.1 m)	6' to 20' (1.8 to 6.1 m)	6' to 20' (1.8 to 6.1 m)
Width, transport	2.5' (762 mm) wider than working width	2.5' (762 mm) wider than working width	2.5' (762 mm) wider than working width	2.5' (762 mm) wider than working width
Weight, per foot	550 lb/ft class (250 kg)	550 lb/ft class (250 kg)	650 lb/ft class (295 kg)	650 lb/ft class (295 kg)
Weight, per blade	242 lb (110 kg)	266 lb (121 kg)	297 lb (135 kg)	340 lb (154 kg)
Horsepower required	6 to 8 DBHP/ft	6 to 8 DBHP/ft	7 to 9 DBHP/ft	7 to 9 DBHP/ft
<b>Structure</b>				
Frame	6" x 4" x 3/8" (152 x 102 x 8 mm)	8" x 4" x 3/8" (203 x 102 x 8 mm)	8" x 4" x 3/8" (203 x 102 x 8 mm)	8" x 4" x 3/8" (203 x 102 x 8 mm)
Gang beam size	6" x 4" x 3/8" (152 x 102 x 8 mm)	6" x 4" x 3/8" (152 x 102 x 8 mm)	6" x 4" x 3/8" (152 x 102 x 8 mm)	6" x 4" x 3/8" (152 x 102 x 8 mm)
Hitch, length	92" (2.33 m)	92" (2.33 m)	92" (2.33 m)	92" (2.33 m)
Hanger, std.	Rigid, U-Bolt Mounted	Rigid, U-Bolt Mounted	Rigid, U-Bolt Mounted	Rigid, U-Bolt Mounted
Hanger, opt. stone flex	1.25" x 2.5" (32 x 64 mm)	1.25" x 2.5" (32 x 64 mm)	1.25" x 2.5" (32 x 64 mm)	1.25" x 2.5" (32 x 64 mm)
Gang shaft	1-15/16" (49 mm)	1-15/16" (49 mm)	1-15/16" (49 mm)	1-15/16" (49 mm)
Spools, steel fabricated	5-1/2" (140 mm) Dia. O.D.	5-1/2" (140 mm) Dia. O.D.	6-5/8" (168 mm) Dia. O.D.	6-5/8" (168 mm) Dia. O.D.
Bearings	410 WSS series	410 WSS / T2-215 series	T2-215 series trunnion mounted, regreaseable, 22,800 lb radial load rating	T2-215 series trunnion mounted, regreaseable, 22,800 lb radial load rating
Gang angle	25°, 22°, 19° F & R	25°, 22°, 19° F & R	25°, 22°, 19° F & R	25°, 22°, 19° F & R
<b>Blades</b>				
Blade sizes, notched/smooth	24" x 5/16" (610 x 8 mm)	24" x 5/16" (610 x 8 mm)	26" x 5/16" (660 x 8 mm)	26" x 5/16" (660 x 8 mm)
Blade sizes, optional, smooth	24" x 5/16" (610 x 8 mm) 26" x 5/16" (660 x 8 mm)	- -	- -	- -
Blade sizes, optional, notched/smooth	26" x 5/16" (660 x 8 mm) -	26" x 5/16" (660 x 8 mm) 26" x 3/8" (660 x 9 mm) 28" x 3/8" (711 x 9 mm)	26" x 3/8" (660 x 9 mm) 28" x 3/8" (711 x 9 mm) 30" x 3/8" (762 x 9 mm)	26" x 3/8" (660 x 9 mm) 28" x 3/8" (711 x 9 mm) 30" x 3/8" (762 x 9 mm)
<b>Features</b>				
Adjustable rigid scrapers	4" High Carbon Steel	4" High Carbon Steel	4" High Carbon Steel	4" High Carbon Steel
Tires	11L x 15 FI	11L x 15 FI	11L x 15 FI	11L x 15 FI
Depth control	Single 4" x 12" (102 x 305 mm) hydraulic cylinder c/w depth control segments	Single 4" x 12" (102 x 305 mm) hydraulic cylinder c/w depth control segments	Single 4" x 12" (102 x 305 mm) hydraulic cylinder c/w depth control segments	Single 4" x 12" (102 x 305 mm) hydraulic cylinder c/w depth control segments

\*Depends on working depth, soil type, field speed, etc.

MODEL	SD750	SD1050
<b>Blade Spacing</b>	12" (356 mm)	14" (356 mm)
Width, working	10' to 20' (3 to 6 m)	9.5' to 15.5' (2.9 to 4.7 m)
Width, transport	2.5' (762 mm) wider than working width	2.5' (762 mm) wider than working width
Weight, per foot	750 lb/ft class (340 kg)	1050 lb/ft class (476 kg)
Weight, per blade	361 lb (164 kg)	636 lb (288 kg)
Horsepower required	12 to 15 DBHP/ft*	20 to 25 DBHP/ft*
<b>Structure</b>		
Frame	8" x 4" x 3/8", ballasted (203 x 102 mm)	10" x 4" x 0.5" (254 x 102 x 13 mm)
Gang beam size	6" x 4" x 3/8" (152 x 102 mm)	10" x 4" x 0.5" (254 x 102 x 13 mm)
Hitch, length	92" (2.33 m), floating hitch	92" (2.33 m), floating hitch
Hanger, std.	Rigid, fabricated steel U-Bolt Mounted	Rigid, U-Bolt Mounted
Gang shaft	1-15/16" (49 mm)	1-15/16" (49 mm)
Spools, steel fabricated	6-5/8" (168 mm) Dia. O.D.	Steel fabricated c/w locking drive lug half spools, keyed
Bearings	T2-215 series trunnion mounted, regreaseable, 22,800 lb (10342 kg) radial load rating	T2-215 series trunnion mounted, regreaseable, 22,800 lb (10342 kg) radial load rating
Gang angle	25°, 22°, 19° F & R	25°, 22° F & R
<b>Blades</b>		
Blade sizes, notched	28" x 3/8" (711 x 9 mm), opt. 30" x 3/8" (762 x 9 mm) notched or smooth	32" x 1/2" (813 x 12 mm)
<b>Features</b>		
Adjustable rigid scrapers	4" x 5/8" (102 x 16 mm) steel	4" x 0.75" (102 x 19 mm) steel
Tires	12.5L x 15 FI	12.5L x 15 FI
Depth control	Single 4" x 12" (102 x 305 mm) hydraulic cylinder c/w depth control segments	Single 4" x 12" (102 x 305 mm) hydraulic cylinder c/w depth control segments

\*Depends on working depth, soil type, field speed, etc.

SD550, SD650, SD750
<b>Standard Equipment</b>
Hitch jack
Gang wrench socket
Furrow filler blades
4" wide scrapers
1-1/4" bearing hangers (high strength steel)
Safety light kit
<b>Optional Equipment</b>
Bearing wear plates
Safety chain
Gang angle adjustment wrench set
Wide pan scrapers
Stone flex hangers (SD550, SD650)
Clevis hitch (SD550, SD650)

SD1050
<b>Standard Equipment</b>
Full floating hitch
Depth control segments
Tires, 12.5 L x 15
Safety light kit
<b>Optional Equipment</b>
Bearing wear plates
Safety chain

Cover page » Model SD650 shown



Your dealer in Africa and the Middle East:

RAC Export Trading      D-36041 Fulda / Germany      Tel. +49 661 6060 82

[www.rac-germany.com](http://www.rac-germany.com)      [info@rac-export.de](mailto:info@rac-export.de)

Illustrations, photographs, and specifications in this brochure are based on the latest information at the time of publication. Design and specification of equipment is subject to change without notice; please contact RAC Export Trading for product information and availability. Products produced by other manufacturers featured in photography are not endorsed by Buhler Versatile Inc. and are intended for image reference only.