

## PM2A (2 AXLES BOGGIE LOWBED SEMI-TRAILERS TO AFRICAN MARKETS)



- Boggie
- Payload:
  - 35/40 ton
- Tare:
  - 11000 kg

### DIMENSIONS

- Length: total 12795 mm; low load deck 9270 mm
- Load deck width 2540 mm with side extensions up to 3500mm
- Gooseneck high: 1350 mm

### STEEL CHASSIS

- 2 Automatic welded main beams linked by steel struts in profile to form the platform
- 2" King pin dismountable (2 positions)
- Mudguards

### LANDING GEAR

- 2 Speeds telescopic



# RAC EXPORT TRADING Germany

[www.rac-export.com](http://www.rac-export.com) Tel.+49 661 606082



## ROLLING EQUIPMENT

- Reinforced boggie suspension 32 ton
- 2 Axle's twin wheels
- Ø 400x200 Drum brakes with automatic adjusters
- 8 Tyres 12R 22,5"

## BRAKING SYSTEM (EC RULES) WITHOUT ABS

- Two lines with manual corrective valve depending on payload
- Mechanic parking brake

## LIGHTING AND SIGNALLING

- 2 Rear lights with 9 functions
- Front and lateral extensible signaling lights and reflectors

## BODY EQUIPMENT

- 6/8 mm non-sleep steel floor
- 2 Hydraulic loading ramps operated by hydroelectric power pack with hydraulic lateral displacement up to 3000 mm
- Width of ramps: 900 mm
- Hydraulic rear feet supports
- Manual hydraulic pump for ramps and rear feets as emergency

## OTHER EQUIPMENT

- 30 l Water tank
- Tools box 600x400x500 mm

## PAINT WORK

- Shot blasting, primary and 2 components final painting



RAC EXPORT TRADING  
Germany

[www.rac-export.com](http://www.rac-export.com) Tel.+49 661 606082



OPTIONS
3.5" King Pin
Access ramps (2) to the gooseneck
More high gooseneck for 1450 mm 5.th wheel tractors
Hydraulic winch
4 Twist-locks
Articulated ramps with 4500 mm
Metallic side boards on the gooseneck
Rigid width of 2750 mm or 3000mm