

PM2A (2 AXLES BOGGIE LOWBED SEMI-TRAILERS TO AFRICAN MARKETS)



- Boggie
- Payload:
 - 35/40 ton
- Tare:
 - 11000 kg

DIMENSIONS

- Length: total 12795 mm; low load deck 9270 mm
- Load deck width 2540 mm with side extensions up to 3500mm
- Gooseneck high: 1350 mm

STEEL CHASSIS

- 2 Automatic welded main beams linked by steel struts in profile to form the platform
- 2" King pin dismountable (2 positions)
- Mudguards

LANDING GEAR

- 2 Speeds telescopic

ROLLING EQUIPMENT

- Reinforced boggie suspension 32 ton
- 2 Axle's twin wheels
- Ø 400x200 Drum brakes with automatic adjusters
- 8 Tyres 12R 22,5"

BRAKING SYSTEM (EC RULES) WITHOUT ABS

- Two lines with manual corrective valve depending on payload
- Mechanic parking brake

LIGHTING AND SIGNALLING

- 2 Rear lights with 9 functions
- Front and lateral extensible signaling lights and reflectors

BODY EQUIPMENT

- 6/8 mm non-sleep steel floor
- 2 Hydraulic loading ramps operated by hydroelectric power pack with hydraulic lateral displacement up to 3000 mm
- Width of ramps: 900 mm
- Hydraulic rear feet supports
- Manual hydraulic pump for ramps and rear feet as emergency

OTHER EQUIPMENT

- 30 l Water tank
- Tools box 600x400x500 mm

PAINT WORK

- Shot blasting, primary and 2 components final painting

| OPTIONS |
|---|
| 3.5" King Pin |
| Access ramps (2) to the gooseneck |
| More high gooseneck for 1450 mm 5.th wheel tractors |
| Hydraulic winch |
| 4 Twist-locks |
| Articulated ramps with 4500 mm |
| Metallic side boards on the gooseneck |
| Rigid width of 2750 mm or 3000mm |