

## PM3A (3 AXLES LOWBED SEMI-TRAILERS REINFORCED TO AFRICAN MARKETS)



- Payload:
  - 60 ton
- Tare:
  - 13000 kg

### DIMENSIONS

- Length: total 12795 mm; low load deck 9270 mm
- Load deck width: 2540 mm with side extensions to 3000 mm
- Gooseneck high: 1350 mm

### OTHER EQUIPMENT

- 30 l Water tank
- Tools box 600x400x500 mm
- Spare wheel support
- Spare wheel 12R22,5

### LANDING GEAR

- 2 Speeds telescopic

## STEEL CHASSIS

- 2 Automatic welded main beams linked by steel profiles and reinforced by round tubes
- Reinforced gooseneck in 25 mm plate thickness
- Lateral profiles in reinforced steel
- 2" King pin dismountable
- Mudguards

## ROLLING EQUIPMENT

- Reinforced mechanic suspension with semi-elliptical leafs
- 3 Axle's 14/16 ton twin wheels
- Ø 400x200 Drum brakes with automatic adjusters
- 12 Tyres 12R22,5"

## BRAKING SYSTEM WITHOUT ABS

- Two lines with corrective valve depending on payload
- Pneumatic parking brake

## LIGHTING AND SIGNALLING

- 2 Rear lights with 9 functions
- Front and lateral extensible signaling lights and reflectors

## BODY EQUIPMENT

- 6/8 mm non-sleep steel floor and hard wood 40 mm
- Hydraulic loading ramps (2), with 900 mm width, operated by hydroelectric power pack with hydraulic lateral displacement up to 3000 mm controlled by hydraulic block valves
- Hydraulic rear feet supports (2)
- Manual hydraulic pump for ramps and rear feet as emergency

## PAINT WORK

- Shot blasting, primary and 2 components final painting

OPTIONS
3.5" King Pin
Access ramps (2) to the gooseneck
More high gooseneck for 1450 mm 5.th wheel tractors
Hydraulic winch
4 Twist-locks for containers 1-20"
Articulated ramps with 4500 mm
Metallic side boards on the gooseneck
Rigid width of 3000mm