

## RPM3 (3 AXLES LOWBED TRAILER)



- Payload: 30 ton
- Hard wood
- Hydraulic displacement on ramps

### DIMENSIONS

- Length: total 8690 mm; low load deck 6435 mm
- Load deck width 2540 mm with turning slide extensions adjustment to 3000 mm

### STEEL CHASSIS

- 2 Automatic welded main beams linked by cross profiles stepped to inlay the floor
- Mudguards with anti-spray protection
- Side under run protections
- Normalized draw bar  $\text{Æ} 40 \text{ mm}$
- DK 90/20 turntable 20 ton axial load and 60 ton maximum gross weight trailer

### LIGHTING AND SIGNALLING

- 2 Rear lights with 9 functions
- Front and lateral extensible signaling lights and reflectors



# RAC EXPORT TRADING Germany

[www.rac-export.com](http://www.rac-export.com) Tel.+49 661 606082



## ROLLING EQUIPMENT

- Pneumatic suspension
- 3 Axle's 13 ton twin wheels
- Ø 300x200 Drum brakes with automatic adjusters
- 12 Tyres 245/70 R17,5"

## BRAKING SYSTEM (EC RULES)

- Two lines with corrective valve depending on payload
- Parking air brake (Maxibrake)
- EBS with 4S3M sensors, RSP system (anti-rollover and help to traction)

## BODY EQUIPMENT

- Pneumatic and braking controlling board at front left side
- 40 mm Hard wood and 6/8 mm non-sleep steel floor
- 2 Hydraulic loading ramps operated by hydroelectric power pack with hydraulic lateral displacement up to 3000 mm controlled by hydraulic block valves with hand lever
- 1 Pole 24 volts plug, for lighting use
- Battery power cables
- Mechanic rear feet support

## OTHER EQUIPMENT

- 30 l Water tank
- Tools box 600x400x500 mm
- Wood for extensions

## PAINT WORK

- Shot blasting, primary and 2 components final painting

