

PRM4 (4 AXLES LOWBED TRAILER)



- Payload: 40 ton
- Hard wood
- Hydraulic displacement on ramps

DIMENSIONS

- Length: total 10190 mm; low load deck 6940 mm
- Load deck width 2540 mm with turning slide extensions adjustment to 3000 mm

STEEL CHASSIS

- 2 Automatic welded main beams linked by cross profiles stepped to inlay the floor
- Mudguards with anti-spray protection
- Side under run protections
- Normalized draw bar Æ 40 mm
- DK 90/20 turntable 20 ton axial load and 60 ton maximum gross weight trailer

LIGHTING AND SIGNALLING

- 2 Rear lights with 9 functions
- Front and lateral extensible signaling lights and reflectors



ROLLING EQUIPMENT

- Pneumatic suspension
- 4 Axle's 13 ton twin wheels
- Ø 300x200 Drum brakes with automatic adjusters
- 16 Tyres 245/70 R17,5"

BRAKING SYSTEM (EC RULES)

- Two lines with corrective valve depending on payload
- Parking air brake (Maxibrake)
- EBS with 4S3M sensors, RSP system (anti-rollover and help to traction)

BODY EQUIPMENT

- Pneumatic and braking controlling board at front left side
- 40 mm Hard wood and 6/8 mm non-sleep steel floor
- 2 Hydraulic loading ramps operated by hydroelectric power pack with hydraulic lateral displacement up to 3000 mm controlled by hydraulic block valves with hand lever
- 1 Pole 24 volts plug, for lighting use
- Battery power cables
- Mechanic rear feet support

OTHER EQUIPMENT

- 30 l Water tank
- Tools box 600x400x500 mm
- Wood for extensions

PAINT WORK

- Shot blasting, primary and 2 components final painting

OPTIONS

Without rear ramps (minus)

Articulated ramps with 4500 mm

